

Certificate of Analysis

BDG Synthesis certifies that this reference material meets or exceeds the specifications stated herein.

leil Beare

Neil Beare, PhD, Director 19 January 2017

Name: Fluticasone Propionate RC E

CAS Number: 220589-37-7

Structure:

Molecular Weight: $C_{43}H_{51}F_5O_8S = 822.92$

Lot Number: BDG 17201.11

Appearance: White, crystalline solid

Corrected Purity: 98.8 % (HPLC) - 5.2 % (water) = 93.6 %

Re-test Date: 19 January 2022

Storage and Handling: Temperature: refrigerate for prolonged storage; may be handled and shipped at

ambient temperature.

Humidity: not believed to be hygroscopic; may be handled in normal laboratory

atmosphere.

Light: protect from strong sunlight.

Caution: only experienced laboratory personnel should handle the material.

Susceptible to static.

Version 2 (1d960) 1/5

Identity and Purity

Proton NMR Spectrum

Identity: the signals are consistent with the proposed structure and in accord with literature where available.

Residual Solvents: no residual solvents are observed.

Impurities: traces of unidentified impurities are seen in the baseline.

Carbon-13 NMR Spectrum

Identity: the signals are consistent with the proposed structure and in accord with literature where available.

High-resolution Mass Spectrum (ESI+)

Found m/z 845.3119. $C_{43}H_{51}F_5NaO_8S$ [M+Na]⁺ requires m/z 845.3123. The deviation of 0.5 ppm is within normally accepted limits for the establishment of identity by HRMS.

HPLC

A somewhat broadened, symmetrical peak is observed (98.8 %). Note: in the absence of reference materials for preparing calibration curves, it is assumed that all peaks have the same detector response. Where possible, the conditions of analysis follow a pharmacopeial or literature method, or have been adapted from same.

Elemental Analysis

Found: C 59.26, H 6.25 %

 $C_{43}H_{51}F_5O_8S\cdot 2.5H_2O$ Requires: C 59.50, H 6.50 %, H_2O 5.19 %

 $C_{43}H_{51}F_5O_8S$ Requires: C 62.76, H 6.25 %

The elemental analyses fall somewhat outside those expected for anhydrous material; the presence of water is reasonably expected from the method of purification and/or the type of material, and the "best-fit" hydrated molecular formula is given. In the absence of a Karl-Fischer water analysis, we recommend that the "best-fit" water content be used when determining corrected purity.

The available quantity of custom-synthesised material is always small, and this limits the extent and type of analytical data which can be obtained. This Certificate is presented in descriptive format for use by analytical chemists who are trained in the use of custom-synthesised materials. Custom materials often contain higher levels of residual solvents and/or water, and we urge you to use the corrected purity where needed rather than the raw HPLC purity. This compound is intended for use as an analytical reference material and it is not for human administration. Structures are shown with relative stereochemistry unless otherwise specified.

The re-test date is assigned from experience gained with the material in the laboratory and/or on storage. It is not possible to perform formal storage studies because of the small amount of material available.

4xCH+CH₂F+ 2xCHF+2xOH 9.8 H

2xCH


2.0 H

ОН 0.9 H


2xOCH

2.0 H






Lot Number: BDG 17201.11







BDG SYNTHESIS



Lot Number: BDG 17201.11





 \mathbf{C}

BDG - Analysis of Fluticasone Propionate RC E


Column: Phenomenex Luna C18(2) 5um 250 x 4.6 mm Guard: Phenomenex Security Guard C18 RP 4 x 3 mm Mobile Phase A: 45:55 Water: Acetonitrile

Mobile Phase B : Acetonitrile

Gradient (A:B): T0=100:0, T30=100:0, T35=0:100, T45=0:100, T46=100:0, T50=100:0

Column Temperature: 30 C Flow Rate: 1.0 mL/min Sample Solvent: Mobile Phase A Injection Volume: 10 uL Detection: UV 239 nm

Sample Name	BDG 17201.11	Instrument	AnalyticalLC01 LC10632y (23)
Acquisition	19/01/2017, 17:02:08	Method (rev.)	
Sequence	BDG_19Jan2017b - Reprocessed	Vial Position	1
Operator	solvation010\cerityadmin	Injection	1 of 1



Area Percent Report

Peak#	RT	Peak Height	Peak Area	Width	Area %
1	20.54 min	0.8364	23.9237	0.3537 min	0.220 %
2	23.20 min	349.3800	10727.9510	0.4702 min	98.816 %
3	24.18 min	2.4737	63.9874	0.3578 min	0.589 %
4	28.35 min	0.1789	5.3223	0.3711 min	0.049 %
5	29.77 min	0.2817	7.5108	0.3271 min	0.069 %
6	30.54 min	0.3755	19.8934	0.6540 min	0.183 %
7	32.59 min	0.1910	7.8714	0.5088 min	0.073 %